



SANSPAR

CAPE TOWN

Tel: 021-5110283 - Email: info@sanspar.co.za

JOHANNESBURG

Tel: 011-3976889 - Email: jhb@sanspar.co.za

DURBAN

Tel: 031-7002485 - Email: kzn@sanspar.co.za

GQEERHA

Tel: 041-4512360 - Email: salespe@effast.co.za

UNI-FLO FLANGED Y-STRAINER



DESCRIPTION

- Face to face dimensions in accordance with DIN 3202 F1
- Flange Dimensions to DIN 2501 PN10/PN16
- Pressure rating PN16 .
- Flange drilling to BS4504 T10/T16 or BS10 TD

DIMENSIONS

DN	L	H	D	MESH DIA
50	230	170	165	1.5
65	290	205	185	1.5
80	310	210	200	1.5
100	350	235	220	2
125	400	270	250	2
150	480	310	285	2
200	600	390	340	2.5
250	600	430	405	2.5
300	650	500	460	2.5
350	980	670	520	2.5
400	1100	780	580	2.5

MATERIALS LIST

	PART	MATERIAL
1	Body	SG Iron to BS420/12
2	Plug	Galvanised Steel
3	Cover	SG Iron to BS420/12
4	Screen	Stainless Steel mesh (304SS)
5	Gasket	Rubber

