



SANS PAR

CAPE TOWN

Tel: 021-5110283 - Email: info@sanspar.co.za

JOHANNESBURG

Tel: 011-3976889 - Email: jhb@sanspar.co.za

DURBAN

Tel: 031-7002485 - Email: kzn@sanspar.co.za

GQEBERHA

Tel: 041-4512360 - Email: salespe@effast.co.za

UNI-FLO NYLON CHECK VALVE



Advanced Re-inforced Polymer Inline Check Valve

Size range:	DN15 - DN50
Pressure rating:	16 Bar
End connection:	Screwed BSPT
Body material:	Advanced re-inforced polymer
Body seal:	EPDM
Seat Seal:	EPDM
Seat Spring	304 Stainless Steel
Temperature Range:	-10°C + 80°C

PARTS AND DIMENSIONS

G	L1	L	H1	H2	H
15	34	47.5	12	12	62
20	41.5	55	13	13	68.5
25	51	63.5	16.5	16.5	81
32	57.5	76	16.5	16.5	99
40	69	86	22	22	103
50	82	99	22	22	120

NO.	PART NAME	NO.	PART NAME
1	NYLON BODY	4	EPDM GASKET
2	NYLON CORE	5	EPDM O-RING
3	PP GASKET	6	304 SPRING

