



## UNI-FLO RISING SPINDLE RSV PN16 SANS 665



### UNI-FLO RSV VALVES

- 665 Rising spindle
- Fusion bonded epoxy coated
- Pressure Rating: 16bar
- Fully encapsulated EPDM disc
- Handwheel or gearbox operated
- Available in flanged

### DIMENSIONS

DN	L	D	b	H	W
50	178	165	19	312	160
80	203	200	19	390	250
100	229	220	19	450	280
150	267	285	19	598	350
200	292	340	20	770	400
250	330	405	22	890	450
300	356	460	24.5	1040	480

### MATERIALS LIST

NO.	PART	MATERIAL
1	Body	S G Iron - BS 420/12
2	Gate	SG Iron - EPDM Encapsulated
3	Gate Nut	Stainless Steel 420
4	Bonnet	S G Iron - BS 420/12
5	Spindle	Stainless Steel 420
6	Packing	Flexible Graphite
7	Gland	S G Iron - BS 420/12
8	Yoke	S G Iron - BS 420/12
9	Spindle Nut	Brass
10	Handwheel	SG Iron - BS 420/12
11	Bonnet Gasket	NBR/EPDM
12	Bonnet Bolts	High tensile steel
13	Sleeve	S G Iron - BS 420/12
14	Gasket	Brass
15	Nut	S G Iron - BS 420/12

