SANSPAR

CAPE TOWN
Tel: 021-5110283 - Email: info@sanspar.co.za
JOHANNESBURG
Tel: 011-3976889 - Email: jhb@sanspar.co.za
DURBAN
Tel: 031-7002485 - Email: kzn@sanspar.co.za
GQEBERHA
Tel: 041-4512360 - Email: salespe@effast.co.za

UNI-FLO SMART CLAMP - STAINLESS STEEL REPAIR CLAMP



FEATURES

- **Unique Assembly Handle**
  Designed for quick and effortless installation.
- **PTFE-Coated SS304 Bolts**
  Prevents thread galling and ensures smooth tightening.
- **Fully Passivated SS304 Construction.**
  Provides superior corrosion resistance and long service life.
- **Gridded EPDM Sealing Rubber with Tapered Ends**
  Facilitates easy installation while delivering a reliable, leak-proof seal.
- **Heavy-Gauge Vulcanized Bridge Plate**
  Permanently bonded into the sealing rubber for maximum strength, stability and sealing.

DIMENSIONS

NB	Code	OD Range (mm)	Band Width (mm)	PVC/HDPE	FIBRE CEMENT	STEEL
40	FC45-55-06	45-55	150	50mm		48.3mm
50	FC59-67-06	59-67	150	63mm		60.3mm
65	FC69-76-06	69-76	150	75mm	AC 50 COD (69mm)	76.1mm
65	FC75-83-06	75-83	150	75mm		76.1mm
80	FC87-93-06	87-93	150	90mm		88.9mm
80	FC95-104-08	95-104	200		AC 75 COD (96mm)	
100	FC104-113-08	104-113	200	110mm		
100	FC113-120-08	113-120	200			114.3mm
100	FC121-130-08	121-130	200	125mm		
125	FC130-142-08	130-142	200	140mm		139.7mm
125	FC145-155-08	145-155	200		AC 125 COD (150mm)	
150	FC150-161-08	150-161	200	160mm		
150	FC167-176-08	167-176	200			165.1mm
150	FC174-183-08	174-183	200		AC 150 COD (177mm)	
175	FC189-199-08	189-199	200			193.7mm
200	FC196-205-08	196-205	200	200mm		
200	FC218-228-08	218-228	200			219.1mm
200	FC229-238-08	229-238	200		AC 200 COD (232mm)	
225	FC254-264-012	254-264	300		AC 225 COD (259mm)	
250	FC248-257-012	248-257	300	250mm		
250	FC271-281-012	271-281	300			273mm
250	FC281-290-012	281-290	300		AC 250 COD (286mm)	
300	FC312-322-012	312-322	300	315mm		

Rev 1 Nov 2026